



PAINTING THE PAST

Paste Wax

Description:

Painting the Past Paste Wax is a white or coloured chalky wax manufactured according to an old recipe with added chalk.

Typical use:

Apply Painting the Past Paste Wax to protect wood. The coloured Paste Wax creates a genuine weathered, antique or aged effect when applied on top of Painting the Past Matt chalk paint.

Most important characteristics:

- * Very easy to apply
- * For use on untreated wood
- * Can also be applied on top of 'matt' chalk paint
- * Easy to maintain
- * Quick drying
- * Authentic recipe

Containers and colours available:

Painting the Past Paste Wax is available in transparent as well as in a range of colours including: White, Grey, Taupe, Cement, Carbon, Pearl, Old White, Loft, Olive, and Antique Wax in 370 ml tins.

Drying time and coverage:

Drying time:

Dry to touch after about 2 hours

Can be repainted:

No

Coverage:

Highly dependent on the surface and application method.

Processing:

Application:

Apply Painting the Past Paste Wax with a brush or cloth.

Temperature:

You can apply Painting the Past Paste Wax at temperatures between 10°C and 25°C.

Preparation:

Paste Wax should be applied to untreated surfaces or surfaces that have a good coat of Painting the Past Matt chalk paint.

The surface to be painted should be clean, dry and dust free.

Remove all loose paint.

Use [Painting the Past Wax & Paint Remover](#) to remove wax and/or old paint in poor condition and then rinse thoroughly with clean water.

Ask a professional for advice or contact Painting the Past (info@paintingthepast.nl or +31 (0)475-335 632) for help with surfaces that are no longer in good condition, for example due to wood rot.

Treating untreated wood indoors or wood painted with Painting the Past Matt chalk paint:

Apply Painting the Past Paste Wax directly onto grease-free wood with a brush or lint-free cloth. Allow the wax to soak in for about 15 minutes and then buff up the surface with a clean, dry, lint-free cloth. If desired, repeat the process described for a more intense effect.

Painting the Past Paste Wax is a maintenance product. If the painted surface is used intensively, apply a new layer of Paste Wax from time to time.

Shelf life:

Unopened and original packaging: 2–3 years in a cool, dry place at temperatures between 5°C and 25°C.

Protect from frost and high temperatures.

Keep left-over wax in a properly sealed container.

We recommend using Painting the Past Paste Wax within 6 months of purchase. After this date we cannot accept any liability for reduced quality of the package contents.

Disposal:

Left-over paint must be properly disposed of in accordance with the prevailing environmental protection legislation and regulations. For further information please contact your municipal environmental services department.

Health and the environment:

All Painting the Past products are environmentally friendly and meet the most recent environmental regulations regarding levels of volatile organic compounds (VOC) in the paint.

Wear protective gloves and ensure adequate ventilation when applying the Paste Wax and when it is drying.

Avoid contact with the skin and eyes. If swallowed, seek medical advice immediately and show this container. May cause lung damage if swallowed.

May cause a dry or cracked skin on repeated exposure. We therefore recommend wearing appropriate gloves while working with Painting the Past Paste Wax.

Keep out of the reach of children.

For further information about Painting the Past Paste Wax and product safety please consult www.paintingthepast.com, phone +31 (0)475-335 632, or consult the safety data sheet on the website.

We have taken the utmost care to ensure the information contained in this data sheet is correct. We do not accept any liability whatsoever for the results as the surface material, use and application method are beyond our control. We are always willing to provide information in advance, ask us at info@paintingthepast.com. The information provided does not discharge users of their own responsibility to check the colour and to conduct their own tests regarding the material to be painted. Neither does this information include any binding legal guarantee of particular characteristics or suitability for a particular application. We therefore do not accept any form of liability for the product performance in such circumstances that is greater than the value of the goods we have supplied. If a new product data sheet is issued this edition will no longer be valid.