



PAINTING THE PAST

Wall Primer

Description:

Painting the Past Wall Primer is a semi-transparent water-based wall primer.

Typical use:

We have developed Painting the Past Wall Primer specially for use as primer under Painting the Past Rustic@. Wall Primer can also be used as primer for fibreglass wallpaper.

Most important characteristics:

- * Good penetrating capacity
- * Ideal on untreated surfaces
- * Virtually odourless
- * Complies with health and safety regulations for professional use indoors
- * Improves cover of next coat of paint
- * Easy to apply
- * Does not contain solvent
- * Quick drying

Containers and colours available:

Painting the Past Wall Primer is available in 1 litre and 2.5 litre containers.

Drying time and coverage:

Drying time:

Dry to touch after 1 to 2 hours

Ready for recoat after 3 to 4 hours

Coverage:

5–12 m² per litre (depending on surface and application method)

Processing:

Application:

Apply Painting the Past Wall Primer with a brush, roller or paint sprayer.

Stir well before use.

Temperature:

You can apply Painting the Past Wall Primer at temperatures between 8°C and 30°C.

Preparation:

The surface to be painted should be clean, dry and dust free.

Remove all loose paint.

Remove any grease, oil or wax using [Painting the Past Wax & Paint Remover](#).

New cement and plaster work must be properly dry before it can be painted.

Clean the surface thoroughly with a sponge and clean water.

Apply Painting the Past Wall Primer undiluted and thinly from the top of the wall downwards. If the surface is highly porous, apply a second coat of Wall Primer.

Shelf life:

Unopened and original packaging: 2–3 years in a dry place at temperatures between 5°C and 25°C.

Protect from frost and high temperatures.

Seal container with left-over product properly or, if appropriate, transfer to a smaller, sealable container.

We recommend using Painting the Past Wall Primer within 6 months of purchase.

After this date we cannot accept any liability for reduced quality of the package contents.

Disposal:

All Painting the Past products are water-based. However, left-over paint may not be washed down the sink. Left-over paint must be properly disposed of in accordance with the prevailing environmental protection legislation and regulations.

For further information please contact your municipal environmental services department.

Health and the environment:

All Painting the Past products are environmentally friendly and meet the most recent environmental regulations regarding levels of volatile organic compounds (VOC) in the paint.

Ensure adequate ventilation when applying the paint and when it is drying.

Avoid contact with the skin and eyes. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.

After contact with skin, wash immediately with soap and water.

Keep out of the reach of children.

For further information about Painting the Past Wall Primer and product safety please consult www.paintingthepast.com, phone +31 (0)475-335 632, or consult the safety data sheet on the website.

We have taken the utmost care to ensure the information contained in this data sheet is correct. We do not accept any liability whatsoever for the results as the surface material, use and application method are beyond our control. We are always willing to provide information in advance, ask us at info@paintingthepast.com. The information provided does not discharge users of their own responsibility to check the colour and to conduct their own tests regarding the material to be painted. Neither does this information include any binding legal guarantee of particular characteristics or suitability for a particular application. We therefore do not accept any form of liability for the product performance in such circumstances that is greater than the value of the goods we have supplied. If a new product data sheet is issued this edition will no longer be valid.