



PAINTING THE PAST

Wax & Paint Remover

Description:

Painting the Past Wax & Paint Remover is a high-quality, ecological water-based remover.

Typical use:

We have developed Painting the Past Wax & Paint Remover specially for safely removing wax, oil, varnish, glue, and water-based paint.

Most important characteristics:

- | | | |
|----------------|-----------------------------|----------------------------|
| * Safe to use | * No harmful vapours | * pH neutral |
| * Non-toxic | * Not corrosive to the skin | * Easy to use |
| * Solvent free | * Effective | * Environmentally friendly |

Containers and colours available:

Painting the Past Wax & Paint Remover is available in 1 litre containers.

Drying time and coverage:

Drying time:

5 minutes to 4 hours (depending on the thickness of the wax or paint)

Coverage:

4–6 m² per litre (depending on surface and application method)

Processing:

Application:

Apply Painting the Past Wax & Paint Remover with a brush or roller.

Temperature:

You can apply Painting the Past Wax & Paint Remover at temperatures between 8°C and 25°C.

Preparation:

Painting the Past Wax & Paint Remover can be used to remove wax and paint. Apply a thick layer (approx. 1 cm) of the whitish gel with a brush and leave to soak. Depending on the surface, this may take 5 minutes to 4 hours. Cover the layer of remover with cling film to speed up the process.

Then the paint or wax can be easily removed using a scraper or abrasive pad. If there are multiple layers or a persistent top layer, repeat the process until you have achieved the desired result.

After removing the paint/wax clean the surface with clean water.

When the surface is dry, it can be sanded and painted.

Tip: Before use, we recommend you test Painting the Past Wax & Paint Remover on a sample of your surface.

Note: When removing multiple layers of paint, apply Painting the Past Wax & Paint Remover multiple times, removing loose paint between applications.

Ask a professional for advice or contact Painting the Past (info@paintingthepast.nl or +31 (0)475-335 632) for help with surfaces that are no longer in good condition, for example due to wood rot.

Surfaces should be degreased and sanded before painting.

Shelf life:

Unopened and original packaging: 2 – 3 years at a temperature of 5°C to 25°C.

Protect from frost and high temperatures.

Transfer any left-over paint to a glass jar or other small container that can be properly sealed.

We recommend using Painting the Past Wax & Paint Remover within 6 months of purchase. After this date we cannot accept any liability for reduced quality of the package contents.

Disposal:

All Painting the Past products are water-based. However, left-over paint may not be washed down the sink. Left-over paint must be properly disposed of in accordance with the prevailing environmental protection legislation and regulations. For further information please contact your municipal environmental services department.

Health and the environment:

All Painting the Past products are environmentally friendly and meet the most recent environmental regulations regarding levels of volatile organic compounds (VOC) in the paint.

Painting the Past Wax & Paint Remover is solvent-free and pH neutral, it consists mainly of water yet is an effective remover of wax, different types of paint and varnish.

Wax & Paint Remover does not contain any harmful vapours and is not toxic.

Painting the Past Wax & Paint Remover is not caustic and will not burn the skin.

There are no Risk or Safety phrases applicable to this product.

Avoid contact with the skin and eyes. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.

Do not reuse contact lenses: these will have been damaged by the remover.

Do not mix with other cleaning products.

Keep out of the reach of children.

For further information about Painting the Past Paste Wax & Paint Remover and product safety please consult www.paintingthepast.com, phone +31 (0)475-335 632, or consult the safety data sheet on the website.

Environment

VOC content, g/l	0.0 g/l
Classification	minimal
Maximum VOC allowed, g/l (VOC 2010)	0.0 g/l
Category	A
pH	neutral

We have taken the utmost care to ensure the information contained in this data sheet is correct. We do not accept any liability whatsoever for the results as the surface material, use and application method are beyond our control. We are always willing to provide information in advance, ask us at info@paintingthepast.com. The information provided does not discharge users of their own responsibility to check the colour and to conduct their own tests regarding the material to be painted. Neither does this information include any binding legal guarantee of particular characteristics or suitability for a particular application. We therefore do not accept any form of liability for the product performance in such circumstances that is greater than the value of the goods we have supplied. If a new product data sheet is issued this edition will no longer be valid.